

# Analysis Method on Network Capacity of Belt Freeway

Shengwen TU<sup>a</sup>, Junjie CHEN and Yao ZHANG

School of Material and Architecture Engineering, Guizhou Normal University, Guiyang, China

**Abstract.** An analysis method on network capacity of belt freeway based on road network reserve capacity is put forward in this paper. Through the introduction of multiple multiplier, the method can simply analyse the maximum traffic volume contained by belt freeway in the conditions of a given network basic demand and meeting the constraints of road traffic capacity and service level. In comparison to the traditional method, the proposed method takes into consideration actual network structure, OD flow distribution, the traveller choosing the way, etc. Additionally, the analysis conclusion is more consistent with the actual situation. Analysis results of belt freeway capacity of Yancheng city in China show that the presented method is not only simple and practical, but also can objectively reflect the status of the belt freeway capacity, and provide a basis for decision-making of belt freeway expansion and urban expressway construction.

## 1 Introduction

The belt freeway has an important position in the group-type urban for connecting traffic organization, almost all through transportation need to pass the belt freeway to realize direction change, parts of entry and exit traffic transportation need to go through the belt freeway for evacuation, parts of long distance transportation between groups can reach the destination through the belt freeway; therefore, traffic volume of most urban belt freeway is quite concentrated, with heavy traffic load. How to conduct quantitative analysis of belt freeway capacity is the real problem faced by planners and decision makers.

The capacity of transportation network means the maximum space transfer capacity of people and objects provided by the entire transportation network within the limits of urban space and given the constraints of transportation facilities resources and environmental capacity, which is also known as the capacity of road network or traffic capacity of road network [1]. Scholars at home and abroad [2-7] have done a lot of researches on analysis calculation of the capacity of road network or traffic capacity of road network, and its main methods are space-time consumption method, linear programming method, cut set method, traffic distribution simulation method, narrow network capacity analysis method, etc. The traditional network capacity calculation model usually regards road network as a simple physical network, only considering the influence of road traffic capacity on the whole network capacity, but ignoring actual structure of road network and the road selection behaviour of users.

## 2 Analysis Method of Belt Freeway Capacity Based on Reserve Capacity of Road Network

In recent years, the concept of road network reserve capacity has aroused a lot of scholars to study capacity of the road network. Given the basic demand of road network  $q_{rs}$  ( $r \in R$ ,  $s \in S$ ,  $R$  and  $S$  belong to O、D set), under the restrictions of meeting road section capacity and service level, if road network can hold the maximum traffic  $\mu \cdot q_{rs}$ , it will be deemed that the multiple multiplier  $\mu$  is reserve capacity of road network. The reserve capacity shows that the adaption of road network to the capacity of a given traffic demand structure; the multiple multiplier  $\mu > 1$  shows that most of current networks have the surplus capacity exceeding the current traffic demand  $(\mu - 1)$  times; the multiple multiplier  $\mu < 1$  shows that network load has overloaded, surpassing the current traffic demand  $(1 - \mu)$  times.

Usually, the problem for solving the network reserve capability can be described by the following bi-level programming problem [6-7].

$$\text{maximize } Z = \mu \quad (1)$$

$$\text{s.t. } v_a(\mu) \leq \rho_a C_a, \forall a \in A \quad (2)$$

Where  $A$  is the set of links,  $\rho_a$  is a parameter denoting the pre-specified LOS required on link  $A$ ,  $C_a$  is the capacity of link  $a$ ,  $v_a(\mu)$  is the flow on link  $a$ , which is obtained by solving the lower-lower user equilibrium (UE) assignment problem under a given reserve capacity multiplier  $\mu$ ,

$$\text{minimize } \sum_{a \in A} \int_0^{v_a} t_a(w) dw \quad (3)$$

<sup>a</sup> Corresponding author: 79418129@qq.com



OD survey data of 2012 and forecast data of 2025 are shown in Table 1 and Table 2 respectively. The design service level of each section of the belt freeway is considered as level 3, that is,  $\rho_a = 0.65$ . The basic

capacity of single-lane freeway is 2000pcu/h, and the coefficient of two-lane in one driving direction is 1.87, then the basic capacity of one driving direction is 3740pcu/h. Peak hour flow ratio is taken 10%.

**Table 1.** The OD Survey Data Between Road Network Nodes in 2012 (pcu/d)

Orig.	Destination									
	1	2	3	4	5	6	7	8	9	10
1	0	1023	339	7742	378	4514	558	609	813	742
2	983	0	327	838	354	2426	307	329	609	103
3	359	337	0	862	103	2317	425	389	359	113
4	7653	848	813	0	1228	5287	508	327	409	106
5	368	345	105	1218	0	772	108	97	229	89
6	4505	2208	2435	5247	802	0	902	708	819	335
7	549	327	416	498	107	922	0	249	349	101
8	634	349	389	307	99	678	229	0	329	231
9	887	689	359	409	209	819	359	309	0	344
10	721	105	102	109	87	341	97	228	351	0

**Table 2.** The OD Forecasting Data Between Road Network Nodes in 2025 (pcu/d)

Orig.	Destination									
	1	2	3	4	5	6	7	8	9	10
1	0	1193	396	9055	440	5283	641	703	960	964
2	1146	0	385	9991	415	2841	359	385	713	121
3	411	394	0	1009	121	2711	497	455	420	132
4	8954	992	951	0	1437	6186	594	383	479	124
5	431	404	123	1425	0	903	126	113	268	104
6	5271	2583	2849	6144	938	0	1055	828	958	392
7	642	383	487	583	125	1079	0	291	408	118
8	742	408	455	359	116	793	268	0	385	274
9	1038	806	431	479	245	956	420	362	0	402
10	844	126	121	128	102	399	113	267	411	0

According to the data of OD of 2012 in Table 1, and substituting the above parameters into Eq.(7)-Eq.(11), the multiple multiplier  $\mu$  of belt freeway in 2012 is calculated to be 1.17, and the V/C value of each link is

shown in Table 3. Similarly, the multiple multiplier  $\mu$  of belt freeway in 2025 is calculated to be 0.92, and the V/C value of each link is shown in Table 4.

**Table 3.** V/C Value of Links (in 2012)

No. of link	1	2	3	4	5	6	7	8	9	10
V/C	0.42	0.49	0.56	0.51	0.48	0.15	0.13	0.13	0.13	0.13
No. of link	11	12	13	14	15	16	17	18	19	20
V/C	0.09	0.08	0.12	0.12	0.12	0.12	0.15	0.48	0.51	0.56

**Table 4.** V/C Value of Links (in 2025)

No. of link	1	2	3	4	5	6	7	8	9	10
V/C	0.49	0.57	0.66	0.74	0.71	0.46	0.45	0.45	0.46	0.51
No. of link	11	12	13	14	15	16	17	18	19	20
V/C	0.44	0.43	0.36	0.46	0.44	0.44	0.46	0.70	0.73	0.65

From the calculate results, it can be seen that Yancheng belt freeway has about 17% of surplus degrees of capacity in 2012. Many road links are at the service of level 1, operating in good condition. In 2025, with the growth of traffic demand, the belt freeway is about more than 8% of capacity according to the predicted traffic demand structure. Some road links will exceed Level 3

service standards, and the running condition of belt freeway will decline sharply. Therefore, it is urgent to improve the construction of the expressway system in the urban area by 2025, and to exert the effect of the urban expressway system on the attraction of entry-exit traffic as well as through traffic, so as to ease the traffic pressure of the belt freeway.

## 4 Conclusions

In order to overcome the limitation of analysis method of traditional road network capacity, a belt freeway capacity analysis method is put forward in this paper based on reserve capacity of the road network, which is applied to the analysis of the capacity of Yancheng belt freeway on 2012 and 2025. The application results show that the proposed method is not only simple and convenient to use, but also takes into account the actual traffic demand structure, the layout of the road network and the route selection behaviour of the travellers, which can reflect the actual loading situation of belt freeway around the city.

For large cities, in addition to the construction of belt freeway, there should also be a complete expressway system, which, together with belt freeway, constitutes a "high speed road" system in the city area. Both of them are responsible for the organizing function of exit-entry traffic and through traffic in city area. Therefore, the problem which need to be studied further is analysing the capacity of belt freeway based on how to consider the synergistic effect of the expressway system and belt freeway, how to consider their division of labour in the external traffic organization.

## Acknowledgement

This research was financially supported by the united fund of Guizhou department of science and technology and Guizhou normal university (Project No. [2016]7225), and also supported by the fund of the doctoral foundation project of Guizhou normal university on 2015.

## References

1. ZHU Jishuang, ZHANG Ning, Analysis of Factors in Affecting the Loading Capacity of Urban Road Networks. *Journal of Transportation Systems Engineering and Information Technology* **8**,1(2008), pp.92-97 (in Chinese)
2. ZHOU Xizhao, LIU Canqi, YANG Peikun. Time-space Sources of the Network of Urban Road and Space-capacity of Traffic. *Journal of Tongji University* **24**,4(1996), pp. 392- 397 (in Chinese)
3. CHEN Chunmei, REN Futian, RONG Jian, TANG Hui. Application of Random Effective Theory to the Study of the capacity of Road Network. *Journal of Beijing Polytechnic University* **28**,4(2002), pp. 436-439 (in Chinese)
4. LI Xuhong, TIAN Feng, GU Zhenghua. Analytical Techniques about the Supply and Demand of Urban Road Network. *Journal of Traffic and Transportation Engineering* **2**,2(2002), pp. 88-90 (in Chinese)
5. Akamatsu, T., Miyawaki, O.. Maximum Network Capacity Problem under the Transportation Equilibrium Assignment. *Infrastructure Planning Review* **12**(1995), pp. 719-729

6. Wong S C, Yang H. Reserve capacity of a signal controlled road network. *Transportation Research Part B* **31**,5(1997), pp. 397- 402
7. Hai Yang, Michael G H Bell, Qiang Meng. Modeling the Capacity and Level of Service of Urban Transportation Networks. *Transportation Research Part B* **34**,4(2000), pp. 255- 275
8. XU Liang, GAO Ziyou. Urban Transport Network Design Based on Link Capacity Reliability. *China Journal of Highway and Transport* **19**,2(2006), pp. 86-90 (in Chinese)
9. ZHU Jishuang, ZHANG Ning. Modeling road network capacity and service level under variable demand pattern. *Systems Engineering-Theory & Practice*, 6(2008), pp. 170-176 (in Chinese)