Free oscillations of thin-walled bimetallic pipelines of large diameter on an elastic foundation

Vladimir Sokolov¹, Igor Razov^{1,*}, and Evgeniy Koynov¹

¹Industrial University of Tyumen, Volodarskogo str. 38, 625001, Tyumen, Russia

Abstract. In the article, solutions are obtained for a thin-walled bimetallic pipeline. Solutions are obtained, and the frequencies of free oscillations are investigated taking into account the internal working pressure, the longitudinal compressive force, and the elastic foundation. The solutions were obtained on the basis of a geometrically nonlinear version of the semi-momentum theory of cylindrical shells of the middle bend. The proposed calculations can find application in the nuclear power industry, aviation, and the petrochemical industry.

1 Introduction

Two-layer steels belonging to the category of bimetals, having a base layer of structural steel and plating of corrosion-resistant, are a unique material combining the required mechanical properties and the necessary corrosion resistance. The main indicators of the quality of double-layer rolling, determining its adaptability in the manufacture of equipment and the operational properties of the product, are the continuity and strength of the joining of the layers, as well as the special properties of the cover layer (corrosion resistance, wear resistance, etc.). The increasing demand for high-performance equipment for oil and gas processing and chemical industries operating in the most extreme conditions (high and low temperatures, pressure, corrosive environments, cyclic loading), necessitates the use of reliable bimetals ensuring compliance with Rostekhnadzor's requirements for fire and explosion hazard facilities and safe operation of equipment for many years.

Bimetallic pipelines have several advantages over single-layered steel, especially in terms of corrosion resistance. Such pipelines can work, as well as single-layer steel, under hazardous dynamic conditions, and therefore this issue is interesting and relevant for the study.

2 Materials and methods

Bimetallic pipelines consist of two layers of metals, most often the main layer is made of strong steels 10, 20, 09G2C, 12XM etc., covering of chromium steels 08X13, 08X14FB and chromium-nickel steels 08X18H10, 08X18H10B etc. The covering layer can be positioned

* Corresponding author: RazovIO@mail.ru

both inside the pipe and / or outside. The location of this layer depends on the field of application of the pipelines, the environmental conditions and the required mechanical characteristics. The main production methods for obtaining bimetallic composites are the following:

1. Cold and hot rolling.
2. Casting.
3. Welding by explosion.
4. Vacuum-diffusion welding.

In addition, there are other methods such as pressing and drawing, soldering, surfacing, electroslag welding, cold welding, diffusion welding, ultrasonic welding, friction welding, but these methods are used much less often. Rolling is used for the production of bimetallic sheets, pipes, profiles, rods. The technology of hot rolling of several layers of metal includes preparation (cleaning, etching, washing, degreasing) and assembling the components of the package, preheating and rolling, cutting, heat treatment, straightening and finishing.

To prevent the oxidation of rolled layers, various methods are used - coatings applied electrolytically, by surfacing or spraying, layers of foil and pyrophoric substances. Magnesium carbonate, metal carbonides, chlorides, iodides and metal fluorides are used as reducing substances. For rolling 16ГC-12Х18Н10Т a mixture of carbon black with liquid hydrocarbons is used in a ratio of 1:4. To ensure better adhesion, intermediate layers (pre-cladding) are also used. Schemes of preliminary laying of bimetallic billets in bags are shown in Figure 1.

Fig. 1. Schemes of preliminary laying of bimetallic billets.

Until recently, the disadvantage of bimetallic large-diameter pipelines was the inability to provide the same properties of the base metal and welded joint, which reduced the operational reliability of the pipes due to insufficient resistance to brittle fracture of the weld and the termination of the ends in the volume heat treatment of the pipes [1]. Also, field and complex laboratory tests of pipes showed that corrosion is most often observed in the place of welded pipelines, while the overall corrosion of the inner surface of the pipe does not exceed 0.01 mm / year and local corrosion is not observed. In this connection, the issue of protection of the welded seam after removal of the bead, by welding a narrow strip of the welded seam, in the place of absence of the clad layer, by arc welding with an automatic tracking system of the process, is topical [2]. But at the present time, there is a technique for producing long-length multilayer bimetallic pipes of large diameter for transportation of hydrocarbons.

However, in the use of these materials, there are also difficulties; metals due to the difference in materials by mechanical and thermophysical properties, the distribution of

stresses across layers can also be successful or unsuccessful. Therefore, before offering such pipes for these or other technical devices, it is necessary to study the general laws of the formation of stress fields in multilayer pipes under different thermal stress loading regimes. In the works of KM Gumerov, the question connected with the stress fields of bimetallic pipelines [3] is studied in detail. In particular, the characteristic cases of operation of pipelines are considered:

The two-layer tube is without internal pressure in a cyclically changing uniform temperature field (without gradients);

- The two-layer pipe is under internal pressure at a constant temperature t_0 ;
- The two-layer pipe is under the influence of internal pressure and a cyclically changing uniform temperature field;
- Two-layer pipe is under the influence of internal pressure in a non-uniform and cyclically changing temperature field.

Also, when using these pipes, an economic question arises, since this type of material is an order of magnitude higher than standard steel pipes, however, due to savings on insulating materials and increased service life of these pipelines in corrosive environments, the use of this type of material is economically viable [4].

3 Results and discussion

Based on the a geometrically nonlinear version of semi-momental theory of cylindrical shells [5-7], are in the deformed stage, the motion equation is:

$$\begin{aligned} \frac{\partial^2 T_1}{\partial \xi^2} + \frac{\partial}{\partial \xi} \left(\tau \frac{\partial M_2}{\partial \theta} \right) - \frac{\partial^2}{\partial \theta^2} \left(\frac{R_2^*}{R_1^*} T_1 \right) - \frac{1}{R^2} \frac{\partial^2}{\partial \theta^2} \left(R_2^* \frac{\partial^2 M_2}{\partial \theta^2} \right) - \\ - \frac{\partial}{\partial \theta} \left(\frac{1}{R_2^*} \frac{\partial M_2}{\partial \theta} \right) + R \frac{\partial X_1}{\partial \xi} - R \frac{\partial X_2}{\partial \theta} - \frac{\partial^2}{\partial \theta^2} (R_2^* X_3) = 0, \end{aligned} \quad (1)$$

$$\text{where } X_1 = -R_0 h \rho_{np} \frac{\partial^2 u}{\partial t^2}, \quad X_2 = -R_0 h \rho \frac{\partial^2 v}{\partial t^2}, \quad X_3 = -R_0 h \rho \frac{\partial^2 w}{\partial t^2} + p_0 - \Psi(\theta) w(\xi, \theta, t).$$

M1 and M2 – bending moments in the longitudinal and cross (circular) directions; T1 и T2 – longitudinal and circumferential tangential forces; κ_2 – change the coordinate lines of curvature θ middle surface; ε_1 и ε_2 – the relative elongation in the direction orthogonal dimensionless coordinates $\xi = x/R$ и θ , where x – coordinate along the longitudinal axis of the shell; τ – twist the middle surface along of the shell; u, v, w – related to the radius R tangentially (along the coordinates ξ и θ) and radial movement of the middle surface of the shell.

$$\rho_{np} = \frac{\gamma_{cp}}{g} \quad - \text{the reduced density of the layers,} \quad \gamma_{cp} = \frac{\gamma_1 h_1 + \gamma_2 h_2}{h} \quad - \text{averaged specific gravity}$$

of a two-layer shell, $h = h_1 + h_2$ - thickness of the entire shell, R_0 - radius of the initial surface of a cylindrical shell.

To move to the solution of the problem in displacements have basic relations semi-momental shell theory:

$$T_1 = (1 - \nu^2) B \varepsilon_1, \quad M_2 = D \chi_2, \quad (2)$$

where E - the elastic modulus of the shell material; ε_1 - longitudinal deformation repose
 in two parts: $\varepsilon_1 = \varepsilon_0 + \frac{\partial u}{\partial \xi}$, $\varepsilon_0 = \frac{F}{EA}$, $B = \frac{1}{1-\nu^2}(E_1 h_1 + E_2 h_2)$, - The reduced rigidity of a two-
 layer shell for tension (compression), $D = \frac{1}{3(1-\nu^2)} \{ E_1 [(h_1 - z_0)^3 + z_0^3] + E_2 [(h_2 + z_0)^3 - z_0^3] \}$,
 $z_0 = \frac{E_1 h_1^2 - E_2 h_2^2}{2(E_1 h_1 + E_2 h_2)}$, - position of the
 reduced rigidity of a two-layer shell for bending. [8],
 neutral surface of the shell.

Fig. 2. Determination of the neutral surface of the shell.

The initial deformation ε_0 determined on the assumption of non-deformable cross-sections of the shell, A – cross sectional area.

The relations between deformations and displacements semi-momentary theory have the form:

$$\frac{\partial v}{\partial \theta} + w = 0; \quad \frac{\partial v}{\partial \xi} + \frac{\partial u}{\partial \theta} = 0; \quad g_2 = \frac{\partial w}{\partial \theta} - v; \quad \tau = -\frac{1}{R_0} \frac{\partial g_2}{\partial \xi}, \quad \chi_2 = -\frac{1}{R_0} \frac{\partial g_2}{\partial \theta}. \quad (3)$$

Substituting the relations (2), (3) into the equation (1), after some transformations, and discarding the nonlinear terms we get the linearized equation of shell in displacements:

$$\frac{\partial^3 u}{\partial \xi^3} + \eta h_v^2 \frac{\partial^3}{\partial \theta^3} (g_2 + \frac{\partial^2 g_2}{\partial \theta^2}) + 2 \frac{\partial^2}{\partial \theta^2} (\frac{\partial^2 w}{\partial \xi^2} \varepsilon_0) - \frac{R_0}{E_0 h} p_0 \frac{\partial^3 g_2}{\partial \theta^3} + \frac{R_0}{E_0 h} \frac{\partial^2}{\partial \theta^2} [\Psi(\theta) w(\xi, \theta, t)] -$$

$$- \frac{R_0^2 \rho}{E_0} (\frac{\partial^3 u}{\partial \xi \partial t^2} - \frac{\partial^2 v}{\partial \theta \partial t^2} - \frac{\partial^4 w}{\partial \theta^2 \partial t^2}) = 0, \quad (4)$$

where u, v, w – components movement the middle surface of the shell, divided by the radius R ; h_v - parameter of the relative thickness of the shell: $h_v = \frac{h}{R_0 \sqrt{12(1-\nu^2)}}$, where ν -

Poisson's ratio

$$\Psi(\theta) = \frac{kR}{\pi} \left[\frac{\varphi_0^3}{3} + \sum_{m=1}^{\infty} \beta_m \cos m\theta \right]; \quad \beta_m = (-1)^m m^{-3} [2\varphi_m \cos \varphi_m - (\varphi_m^2 - 2) \sin \varphi_m]; \quad \varphi_m = m\varphi_0.$$

$m = 1, 2, 3, \dots$, $\eta = \frac{E_v}{E_0}$, $E_v = \frac{(1-\nu^2)D}{h^3}$, - reduced modulus of elasticity of a two-layer shell for

bending, $E_0 = \frac{(1-\nu^2)B}{h}$, - reduced modulus of elasticity of a two-layer shell for tension (compression).

The obtained system of equations (4) it contains four unknown functions of coordinates and time t : u, v, w and ϑ_2 . Solving this system the variables separation method (Fourier method), we represent the function $w(\xi, \theta, t)$ in the case of hinged support end of shell, obeying the condition of periodicity on the circumferential coordinate θ :

$$w = \sum_m \sum_n f(t) \sin(\tilde{\lambda}_n \xi) \cos(m\theta), \quad (5)$$

where $\tilde{\lambda}_n = \frac{n\pi R}{L}$; $m, n = 1, 2, \dots$ - wavenumbers in the circumferential and longitudinal directions. The other components of displacement and rotation angle of the tangent determined from the relations semi-momental shell theory (3):

$$\begin{aligned} u &= - \sum_m \sum_n \frac{\tilde{\lambda}_n}{m^2} f(t) \cos(\lambda_n \xi) \cos(m\theta), & v &= - \sum_m \sum_n \frac{1}{m} f(t) \sin(\tilde{\lambda}_n \xi) \sin(m\theta), \\ \vartheta_2 &= - \sum_m \sum_n \frac{m^2 - 1}{m} f(t) \sin(\tilde{\lambda}_n \xi) \sin(m\theta). \end{aligned} \quad (6)$$

Assuming that free vibrations of a shell is harmonic, then we have:

$$f(t) = \sin \omega_{mn} t, \quad f''(t) = -\omega_{mn}^2 \sin \omega_{mn} t, \quad (7)$$

where ω_{mn} - circular frequency of the shell on the form of the free bending vibrations $m, n = 1, 2, 3, \dots$

Substituting (5) - (6) into the equation (4) and calculate the derivatives entering into the equation:

$$\begin{aligned} \frac{\partial^3 u}{\partial \xi^3} &= - \sum_m \sum_n \frac{\tilde{\lambda}_n^4}{m^2} f(t) \sin \lambda_n \xi \cos m\theta, \\ \frac{\partial^5 \vartheta_2}{\partial \theta^5} &= \sum_m \sum_n m^4 (m^2 - 1) f(t) \sin \lambda_n \xi \cos m\theta, \\ \frac{\partial^3 \vartheta_2}{\partial \theta^3} &= - \sum_m \sum_n m^2 (m^2 - 1) f(t) \sin \lambda_n \xi \cos m\theta, \\ \frac{\partial^3 u}{\partial \xi \partial t^2} &= \sum_m \sum_n \frac{\tilde{\lambda}_n^2}{m^2} f''(t) \sin \lambda_n \xi \cos m\theta, \\ \frac{\partial^3 v}{\partial \theta \partial t^2} &= - \sum_m \sum_n f''(t) \sin \lambda_n \xi \cos m\theta, \\ \frac{\partial^4 w}{\partial \theta^2 \partial \xi^2} &= \sum_m \sum_n m^2 \tilde{\lambda}_n^2 f(t) \sin \lambda_n \xi \cos m\theta, \\ \frac{\partial^4 w}{\partial \theta^2 \partial t^2} &= - \sum_m \sum_n m^2 f''(t) \sin \lambda_n \xi \cos m\theta, \end{aligned} \quad (8)$$

The result of differentiation of the term $\frac{\partial^2}{\partial \theta^2} [\Psi(\theta)w(t, \xi\theta)]$ we represent it as a product of partial sums. First, we multiply the series, and then compute the derivative by general rules. We introduce two partial sums:

$$S_1 = \sum_m a_m \cos(m\theta); \quad m = 1, 2, 3, \dots \quad a_0 = 0.$$

$$S_2 = b_0 + \sum_m b_m \cos(m\theta); \quad b_0 = \frac{\varphi_0^3}{3}; \quad b_m = \beta_m.$$

Next we obtain:

$$Z = S_1 S_2 = z_0 + \sum_{k=1}^{\hat{m}} z_k \cos k\theta,$$

The differentiation of the sum reduces to the differentiation of the terms:

$$\frac{\partial}{\partial \theta} Z = - \sum_{k=1}^{\hat{m}} z_k k \sin k\theta. \quad \frac{\partial^2}{\partial \theta^2} Z = - \sum_{k=1}^{\hat{m}} z_k k^2 \cos k\theta.$$

For further calculations, we pass to the notation $k = m$, as a result we obtain:

$$\frac{R}{Eh} \frac{\partial^2}{\partial \theta^2} (\Psi(\theta)w(\xi, \theta, t)) = \frac{kR^2}{\pi Eh} f(t) \sum_{m=1}^{\infty} m^2 z_m \cos m\theta, \quad (9)$$

where φ_0 is given by (2.8), $\beta_m = (-1)^m m^{-3} [2\varphi_m \cos \varphi_m - (\varphi_m^2 - 2) \sin \varphi_m]$,

$\varphi_m = m\varphi_0$, k – coefficient of soil $[N/m^3]$, m – circumferential wave number.

Next equating the coefficients of like trigonometric functions $\cos m\theta$ at $m = 1, 2, 3 \dots$, we obtain an infinite system of homogeneous linear algebraic equations for the unknown amplitude values b_m of radial displacement component w .

$$\left\{ \tilde{\lambda}_n^4 + \eta m^4 (m^2 - 1)(m^2 - 1 + \frac{p^*}{\eta}) + k^* m^4 - 2\varepsilon_0^* \tilde{\lambda}_n^2 m^4 \right\} f(t) +$$

$$+ \rho_{np}^* R_0 h [\tilde{\lambda}_n^2 h_v + m^2 + m^4] f''(t) = 0, \quad (10)$$

where $\tilde{\lambda}_n = \frac{n\pi R_0}{L\sqrt{h_v}}$, $p^* = p \frac{R_0}{E_0 h h_v^2}$, $\rho^* = \rho_{np} \frac{R_0}{E_0 h h_v^2}$, $\varepsilon_0^* = \frac{F}{E_0 A h_v^2}$, $k^* = \frac{R_0^2 k}{\pi E_0 h h_v^2} z_m$.

add (7) to (10) the receive:

$$\tilde{\lambda}_n^4 + \eta m^4 (m^2 - 1)(m^2 - 1 + \frac{p^*}{\eta}) + k^* m^4 - 2\varepsilon_0^* \tilde{\lambda}_n^2 m^4 - \rho_{np}^* R_0 \cdot h (\tilde{\lambda}_n^2 h_v + m^2 + m^4) \omega_{mn}^2 = 0$$

We transform the term $2\varepsilon_0^* \tilde{\lambda}_n^2 m^4$, taking into account the values of the cross-sectional area of a thin-walled tube $A = 2\pi R h$ and the axial moment of inertia $I = \pi R^3 h$, as a result of the transformations, we obtain:

$$\begin{aligned} & \tilde{\lambda}_n^4 + m^4(m^2 - 1)(m^2 - 1 + p^*) + k^* m^4 - \tilde{\lambda}_n^4 m^4 P / n^2 - \\ & - \rho^* R \cdot h(\tilde{\lambda}_n^2 h_v + m^2 + m^4) \omega_{mn}^2 = 0, \end{aligned} \quad (11)$$

where $P = F / F_g$.

Transforming (11) we obtain the general expression for the square of the frequency of free oscillations ω_{mn}^2 rectilinear section of the pipeline (12) allowing to investigate the influence of internal working pressure, the parameter of the longitudinal compressive force, geometrical characteristics and the effect of the elastic foundation of the soil on the frequencies of free vibrations of a bimetallic surface pipeline of finite length L :

$$\omega_{mn}^2 = \frac{\tilde{\lambda}_n^4 + \eta m^4(m^2 - 1)(m^2 - 1 + \frac{P}{\eta}) + k^* m^4 - \tilde{\lambda}_n^4 m^4 P / n^2}{\rho_{np}^* R_0 \cdot h(\tilde{\lambda}_n^2 h_v + m^2 + m^4)}, \quad (12)$$

where $P = \frac{F}{F_e}$ – dimensionless parameter of the longitudinal compressive force, $F_e = \frac{\pi^2 EI}{L^2}$ Euler force, $\tilde{\lambda}_n = \frac{n\pi R_0}{L\sqrt{h_v}}$

If we equate the frequency to zero, we express the parameter of the internal working pressure:

$$p^* = \frac{-\tilde{\lambda}_n^4}{m^4(m^2 - 1)} + \frac{\tilde{\lambda}_n^4 P / n^2 - k^*}{m^4(m^2 - 1)} - \eta(m^2 - 1) \quad (13)$$

The obtained expression makes it possible to determine the critical pressure parameter at which the frequency of free oscillations is zero and the dynamic stability of the pipeline.

4 Conclusion

1. Based on the geometrically nonlinear variant of semi-momental theory of cylindrical shells solved the problem of determining the frequency of free vibrations of a thin-walled bimetallic pipeline of large diameter, which interacts with the elastic foundation. The solution take into account the impact of the internal operating pressure, the geometric characteristics of the parameter of the longitudinal compressive force, and the influence of elastic resistance on the ground.

2. The obtained solution makes it possible to investigate the influence of materials of a two-layer shell on the frequencies of free oscillations depending on their density, moduli of elasticity and thickness.

3. It was found that the coefficient η an increase or decrease in the critical value of the parameter of the internal operating pressure p^* , which indicates a change in the rigidity of the shell material in the longitudinal and circumferential directions.

The corresponding results in this article were obtained during the execution of the state task of the Ministry of Education and Science of Russia 7.4794.2017/8.9.

References

- 1 A.V. Safyanov, A.A. Fedorov, Pattenet RU№2012155948/02 (2012)

- 2 A.I. Zajcev, I.G.Radionova, A.V. Amežnov, A.A. Pavlov, Tehn. Kolesn I gus mashin **3** (2013)
- 3 A.L. Bikbulatov, R.R. Bagmanov, K.M. Gumerov, Problemi sbora neft. Productov **2**, 120-126 (2015)
- 4 F. Li, B. Wei, X. Zhao, X. Shao, R. Cai, Trenchless Technology - The Best Choice for Underground Pipeline Construction and Renewal, *Proceedings of the International Conference on Pipelines and Trenchless Technology* (2013)
- 5 E.L. Aksel'rad, V.P. Il'in, *Raschet truboprovodov* (Mashinostroenie, 1972)
- 6 V.G. Sokolov, I.O. Razov, Vest. grazhd. Inzh. **6** (2016)
- 7 V.G. Sokolov, *Kolebaniya, staticheskaya i dinamicheskaya ustoychivost' truboprovodov bol'shogo diametra: dis. doktor. tekhn. Nauk* (Spb, 2011)
- 8 V.G. Sokolov, Prom.grajd.stroit **8** (2010)