

Erratum to: Influence of additives on properties of concrete with recycled aggregate and fly ash

Małgorzata Wydra^{1,a}

¹Faculty of Civil Engineering, Mechanics and Petrochemistry (Plock), Warsaw University of Technology, Pl. Politechniki 1, 00-661 Warszawa, Poland

Original article: MATEC Web of Conferences **196**, 04085 (2018), <https://doi.org/10.1051/mateconf/201819604085>

1. The table 2 should be corrected:

Table 2. Mixture proportions for 1 m³ of concrete [kg]. [16]

Component/mixture	REC1	REC2	REC3	REC4
CEM III/A 42.5N	300	300	300	300
Fly ash	200	200	200	200
Microsilica	0	50	0	0
Metakaolin	0	0	50	0
Fluidized fly ash	0	0	0	50
Natural sand 0-2	538	505	509	498
Natural sand 2-4	196	184	185	181
RCA 4-8	369	347	349	342
RCA 8-16	443	416	419	409
SP FK-88	8	9	9	9
Water	172	186	185	183
(W+SP)/(C+P)*	0.360	0.390	0.388	0.384
W/C*	0.573	0.620	0.617	0.610

*Previous to mixing RCA has been saturated, the saturation water is NOT incorporated in the ratio.

1. The caption in the 2 chapter should be corrected:

Fig. 1. Sorptivity test [16]

2. The captions in the 3 chapter should be corrected:

Fig. 3. Damaged specimens after 130 cycles [16]

Table 3. Results of compressive strength tests [16]

Table 4. Results of frost resistant tests – relative decrease of compressive strength [16]

Table 5. Results of sorptivity and absorability tests [16]

3. The following sentence in the 4 chapter should be added

Author wishes to thank Mr. Patryk Tomczak for help in preparing specimens and carrying out tests.

4. Corrected list of references:

^aCorresponding author: malgorzata.wydra@pw.edu.pl

References

1. W. Kubissa, R. Jaskulski and P. Reiterman, *J. of Renewable Mater.*, Volume **5**, Supplement 1, January (2017), pp. 53-61(9).
2. W. Kubissa, T. Simon, R. Jaskulski, P. Reiterman, M. Supera, *Procedia Eng.*, **172** (2017) 595 – 603.
3. G. Fathifazl, A. Abbas, A. G. Razaqpur, O. B. Isgor, B. Fournier, S. Foo, *J. Mater. Civ. Eng.*, **21** (10) (2009) 601-611.
4. K.-H. Yang, H.-S. Chung, A. F. Ashour, *ACI Mater. J.*, **105** (3).
5. L. Evangelista, J. De Brito, *Cem. Concr. Compos.*, **29** (5) (2007) 397-401.
6. S. C. Paul, G. P. van Zijl, *Int. J. Sustainable Constr. Eng. and Technol.*, **4** (1) (2013) 89-103.
7. I. B. Topcu, S. Sengel, *Cem. Concr. Res.*, **34** (8) (2004) 1307-1312.
8. M. Limbachiya, T. Leelawat, R. Dhir, *Mater. Struct.*, **33** (9) (2000) 574-580.
9. J. Jain, K. P. Verian, J. Olek, N. Whiting, *J. Transp. Res. Board*, **2290** (1) (2012) 44-51.
10. S. Abukersh, C. Fairfield, *Constr. Build. Mater.*, **25** (10) (2011) 4088-4094.
11. K. McNeil, T. H.-K. Kang, *Int. J. Concr. Struct. and Mater.*, **7** (1) (2013) 61-69.
12. P. A. Claisse, J. G. Cabrera, D. N. Hunt, *Adv. Cem. Res.*, **13**, No. 4, October, (2001) 165-174.
13. M. Dąbrowski, M. A. Glinicki, *Roads and Bridges*, **12** (2013) 41-55.
14. B. Łaźniewska – Piekarczyk, *Cem. Wapno Bet.* May-June **3** (2013).
15. J. Babińska, *Build. Res. Inst. Q.*, **4** (160) (2011).
16. P. Tomczak, *Eng. Thesis*, Warsaw University of Technology (2017).