

Mode choice model for public transport (ferry, fast ship and aircraft) study case: Kupang - Rote Route

Margareth E. Bolla^{1,*}, Rossy A. Bella², Aprianto Nomleni³, and Desy Yuliaty Tungga²

¹Doctoral Study Program of Civil Engineering, Faculty of Engineering, Brawijaya University, Malang, Indonesia

²Civil Engineering Department, Faculty of Science and Engineering, Nusa Cendana University, Kupang, Indonesia

³Magister Study Program of Water Resources Engineering, Faculty of Engineering, Brawijaya University, Malang, Indonesia

Abstract. The mode of transportation that travels from Kupang City to Rote Ndao Regency is currently a mode of sea transportation and air transportation. This study aims to find out user information based on its mode choices and model it in the multinomial log function, besides that it's hoped that this result can be used as a reference in determining policies that improve functions and facilities for mobilizing people, goods and services carried out on the Kupang to Rote. Data analysis was carried out in two ways, namely with descriptive statistical analysis techniques to explain the characteristics of respondents and multinomial logistic regression analysis to create a model of mode transportation selection for Kupang-Rote service. The results of the study showed that users of transportation services from Kupang to Rote, generally men prefer to use ferry boats while women prefer to use fast boats. The characteristics of respondents is age 20-39 years. While the factors that influence the choice of transportation are the influence of luggage, weather and comfort. For the selection model, the probability of a speedboat is 34.65%, the probability of choosing a ferry is 42.96%, and the probability of choosing an aircraft is 22.3%.

1 Introduction

East Nusa Tenggara Province (NTT) has 427 islands, including Rote Island. Formerly Rote was included in Kupang Regency, but since 2002 it has been established as Rote Ndao District. Rote Ndao itself is Indonesia's southernmost island which borders Australia. Geographical conditions between Rote Ndao District and Kupang City which are separated by the sea cause traffic movement to fulfill the needs of goods and services between islands. The mode of transportation that travels from Kupang City to Rote Ndao Regency is currently a mode of sea transportation and air transportation, whether by plane, ferry boat or fast ship. The main sea ports in Rote Ndao Regency are Baru Beach and Baa. Consideration of transportation selection certainly depends on factors that can affect service user satisfaction. The factors used in the study include income, age, gender, purpose of travel, terminal waiting time, travel time, travel costs, and service level. From the results of his research, the factors that have a significant influence in making modal choices are departure time, travel costs and also reasons for traveling[1]. By adopting the above significant factors accompanied by the addition of several other factors such as distance traveled, luggage and weather influences, then the modeling of transportation mode selection between ferries, speedboats

and aircraft serving Kupang departure route to Rote analysis is carried out. This study aims to find out user information based on the choice of mode and model it in multinomial log functions, where to find out the characteristics of the users of the transportation mode for the Kupang - Rote route and find out the factors that influence the choice of transportation modes between ferries, fast boats and planes in the Kupang - Rote route, besides that this result can be used as a reference in determining policies that improve functions and facilities to mobilize people, goods and services carried out on the Kupang to Rote route.

2 Model of mode selection

2.1 Model definition

In the transportation planning process, one step that must be done is analyzing each relevant data and information as a basis for predicting what will happen in the future. This data and information can be secondary data that obtained from related agencies, or as primary data can be obtained from direct observation on location of research or in reality[4]. Primary data obtained from direct observing activities is difficult to analyze and cannot be used as a basis for predictions of incident and results in the future [4]. For necessity of estimation of these results,

* Corresponding author: margaretachristami@gmail.com

this realistic data and information needs to be simplified as optimally as possible, without deviating from the intent, purpose, and substance of the relevant data and information. Summarize and simplify the realistic conditions activities are known as modeling activities. Thus, the model can be defined as follows [4]:

- The model is a concise representation of the real conditions and tangible forms of design that can explain or represent the real conditions for a particular purpose [2].
- Model is a representation or formalization in certain agreed languages upon from a particular condition [6].
- Model is a main framework or formalization of information / data about collected real conditions to study / analyze the real system [3].

Therefore, the model is a tool that can be used to represent and simplify a reality. The simplification of reality aims to provide a deeper explanation and for the purposes of forecasting.

2.2 Utilities

Value of travel satisfaction in using alternative modes of transportation, influenced and related to variables that are considered to have a strong relationship with the behavior of the traveler and the form of the relationship can be seen through the utility functions are as follows[4]:

$$U=f(V_1, V_2, V_3, \dots, V_n) \quad (1)$$

Where :

U = The value of the traveler's utility using transportation modes

V1 to Vn = Variables that are considered to influence the value of satisfaction using certain modes of transportation

F = Mathematical functional relationship

The activity of determining and observing the behavior of the traveler through the utility function can be done with two approaches. The approach that used determines the probability choice model. Both approaches are:

2.2.1 Aggregate approach

The aggregate approach is an approach that analyzes the behavior of the traveler as a whole. The aggregate approach can be done in two ways, namely [4]:

- Divide the object of observation on several groups that have the characteristics of relatively homogeneous elements (the same).
- Aggregate the disaggregate data, which functions for a particular group can be derived from individual utility functions as members of the group.

2.2.2 Disaggregate approach

The disaggregate approach is an approach that analyzes the behavior of individual travelers. This includes how to formulate individual behavior into the model of transportation needs. The disaggregate approach can be done in two ways, namely [4]:

- a. Deterministic Disaggregate

This approach is carried out if the traveler is able to identify all available alternative modes and use all information to make decisions. The form of the model is a model of multiple linear equations without elements of errors as follows:

$$U_i = a + b_1T + b_2X + b_3C \quad (2)$$

Where:

U_i = satisfaction value using i mode

T = time variable on the vehicle

X = time variable outside the vehicle

C = variable transportation costs

a = constant

b₁ to b₃ = parameter of satisfaction function for each variable (regression coefficient).

b. Stochastic Disaggregate

In this approach, the value of satisfaction is more realistic because it considers the unobservable elements that occur in the reality. All unobservable elements that occur in the reality, in this approach is represented by an element of error (random) that is random or stochastic, so the model becomes:

$$U_m = \beta_0 + \beta_{1tm} + \beta_{2xm} + \beta_{3cm} + en \quad (3)$$

Where:

U_m = value of satisfaction function using m mode

tm-cm = value of satisfaction function using m mode

β₁-β₃ = value of satisfaction function using m mode

en = error factor or stochastic element, that is a random variable that follows a certain distribution form

β₀ = characteristic constants of alternative satisfaction values, if all variables tm to vm are zero. Forecasting is said to be relatively precise, if the en value is at least close to zero (to a minimum) or en = 0

2.3 Multinomial logit model (MNL)%

This model is the most famous and popular discrete choice model. Multinomial logistic regression is a logistic regression where the dependent variable currently has a scale that is polycotomic or multinomial. Thus, this model was chosen because there are more modes for private vehicles, microbus, taxi, motorcycle, etc. Multinomial regression is a form of a model with a relationship function logit where the response is in the form of Nominal qualitative data with more than two categories. The characteristics are carried out between categories of responses are unordered, meaning that between categories there is no level and the nature. Beside that Multinomial regression is more specific to models more than 2 compare with standard method that only calculates the equation model with the Logit form link function where the response is in the form of nominal quality data with the number of categories equal to two or below. Regression models with variables that are nominally sourced are different from the categories of codes 1, 2 and 3. The existing Y variables are parameterized into three functions. The logistic model is a logarithm of opportunities that occur in forms of models described through algorithms [4]:

$$P(i) = \frac{e^{U_i}}{e^{U_i} + \sum_j e^{U_{jn}}} \quad (4)$$

Where :

- P (i) = Opportunity *i* mode to be selected
- U_i = Value of the benefits of using *i* mode
- U_{jn} = Total benefits value of other modes besides *i* mode. (Moda *j*1, *j*n)
- e = Exponent

2.4 Sample determination

To determine the amount of samples from a population, can used the Slovin formula is as follows [7]:

$$n = \frac{N}{1 + N \cdot d^2} \quad (5)$$

Where :

- n = number of samples
- N = number of population
- d = percent error rate (*d* value = 10%)

2.5 Population and sample

2.5.1 Population

Population is an area of generalization consisting of objects / subjects that have certain qualities and characteristics determined by researchers to be studied and then drawn conclusions [5]. The population in this study consisted of two populations that were distinguished based on the location of the study, namely the population of transportation service users from Kupang to Rote. Population data for users of transportation services both from Kupang is shown in Table 1 and Table 2.

Table 1. Recapitulation of fast ship and ferry ships in 2016

No.	Month	Total passenger Fast Ship (Person)	Total passenger Ferry (Person)
		Kupang-Rote	Kupang-Rote
1	January	1957	8862
2	February	2096	8518
3	March	3488	12953
4	April	4130	19702
5	May	3925	30585
6	June	5162	34026
7	July	3923	43057
8	August	4507	36367
9	September	5598	33314
10	October	5201	32633
11	November	4884	28867

No.	Month	Total passenger Fast Ship (Person)	Total passenger Ferry (Person)
		Kupang-Rote	Kupang-Rote
12	December	2488	31780
Total		47359	46301

Source: Bahari express 2016 passenger data and production data of PT. Kupang ASDP in 2016

Table 2. Aircraft passenger recapitulation in 2016

No	Rute	Jumlah Penumpang (Org)
1	Kupang-Rote	21277

Source: UPBU D.C Air transport traffic data. Saudale-rote

Based on the data of passenger recapitulation for each mode of transportation both from Kupang and from Rote, the population can be calculated for 1 area of the research location as follows:

Population_{Kupang} = JP fast ship+ JP plane + JP ferry boat

Description:

jp = number of passengers

So, the following results are obtained:

Populasi_{kupang} = 47,359 people + 21,277 people + 320,664 people

Populasi_{kupang} = 389,300 people

2.5.2 Sample

Sample is a part of the amount and characteristics owned by the population [4]. Based on existing population data, the sample calculation is carried out as followsequation 5. In each study area there are 3 points of the research location, in Kupang consists of Tenau Harbor, Bolok Port and Eltari Airport while in Rote it consists of Ba'a Port, New Beach Harbor and D.C Saudale Airport. Then, the amount of respondents for each study area was divided into 3 parts. One hundred respondents from Kupang were divided into 3 locations, each location received 33.33 or equal to 34 respondents. However, in this study 35 respondents were selected for each research location, likewise withRote area the questionnaire distributed for each location in Rote was 35 questionnaires. So that the questionnaires distributed to respondents in Kupang and in Rote amounted to 150 questionnaires (can be seen in Table 3)

Table 3. Amount of Research Samples

Location	No .	Moda	Amount of Sample	Total of Sample
Kupang	1	Fast Ship	35	105 sample
	2	Aircraft	35	
	3	Ferry	35	

3 Data collection techniques

Primary data is obtained from the results of questionnaire surveys in the field. Distribution of questionnaires was given to respondents who were ferry service users, speed boats and aircraft. The questionnaire survey was conducted at the port and airport waiting room. For aircraft departing from Kupang the questionnaire survey was carried out in the waiting room of Eltari International Airport. Ferry boats were also carried out in the waiting room and also in ships at Bolok Port (which departs from Kupang). Meanwhile, a survey of fast boat service users was carried out in the waiting room and in ships in Tenau Port (passengers from Kupang to Rote). The form of the survey form questions includes two things. First, questions are made to determine the characteristics of the users of transportation services and the characteristics of the transportation system of the three modes of transportation. Second, questions are made to find out the respondents' preferences towards alternative modes of transportation selection with several types of changes in conditions offered.

3.1 Primary data

Primary data is data that can be used directly from the original source. The primary data in this study were sourced from the results of a survey of needs for ferry passengers, speedboats and planes from Kupang and from Rote. The data that will be obtained from the survey results in each access mode are as follows:

- Characteristics of Respondents
 The characteristics of the data collected are as follows age, work, travel purpose, reasons for choosing transportation, travel frequency, monthly income, distance and travel time from the place of origin to the airport or port, distance and travel time from the airport or port to the destination and estimated total transportation costs in traveling
- Service user preferences for service attributes collected are as follows Cost (X1), Travel time (X2), Luggage (X3), Weather (X4) and Comfort (X5)

3.2 Secondary data

Secondary data is data obtained from relevant agencies, in this case from PT. ASDP (River Lake and Crossing Transportation) Kupang Branch and Rote Supervision, Bahari Express Private Ship Company, PT. Angkasa Pura I, UPBU DC. Saudale Rote and literature studies that discuss research topics. The data obtained includes data on fleet numbers, type of fleet, number of passengers per day, tariffs and frequency of services, ferry boats and fast boats that serve Kupang – Rote.

4 Data analysis techniques

Survey data that has been collected is then processed so it can be used as input data in the analysis process using the IBM SPSS version 23 application program. Data analysis is done in two ways, namely descriptive statistical analysis techniques to explain the characteristics of respondents and multinomial logistic regression analysis

for make a model of choosing the transportation modes for Kupang-Rote service route.

After the equation model is obtained, the statistics are tested to find out whether the mode selection equation is feasible to use. Then do the probability calculation of each mode selection for Kupang to Rote route and the opposite route. The probability calculation of each mode is in accordance with equation 6,8,10 which in this study was carried out on ferries, fast ships and aircraft. The modal choice probability calculation formula is as follows:

$$P(\text{ferry}) = \frac{e^{U_{\text{fast ship}}}}{e^{U_{\text{ferry}}} + e^{U_{\text{fast ship}}} + e^{U_{\text{aircraft}}}} \quad (6)$$

$$U_{\text{kapal feri}} = (\beta_1.X_1) + (\beta_2.X_2) \dots + (\beta_n.X_n) \quad (7)$$

$$P(\text{fast ship}) = \frac{e^{U_{\text{fast ship}}}}{e^{U_{\text{ferry}}} + e^{U_{\text{fast ship}}} + e^{U_{\text{aircraft}}}} \quad (8)$$

$$U_{\text{fast ship}} = (\beta_1.X_1) + (\beta_2.X_2) \dots + (\beta_n.X_n) \quad (9)$$

$$P(\text{aircraft}) = \frac{e^{U_{\text{aircraft}}}}{e^{U_{\text{ferry}}} + e^{U_{\text{fast ship}}} + e^{U_{\text{aircraft}}}} \quad (10)$$

$$U_{\text{aircraft}} = (\beta_1.X_1) + (\beta_2.X_2) \dots + (\beta_n.X_n) \quad (11)$$

Where :

- P (i) = Probability *i* mode to be selected (mode *i*: ferry, fast ship and aircraft)
- U_i = Utility value using *i* mode
- E = Exponent

4.1 Multinomial logistic regression analysis

Multinomial Logit Analysis of Kupang-Rote Service Routes. The utility function equation between fast boats, ferries and aircrafts is affected by five factors such as costs, travel time, luggage, weather and comfort. The general form of the model is in accordance with equation (2.2) as described in chapter two points 2.4.2. So in this study the form of utility equations from Kupang to Rote service route are as follows:

$$Y = a + b_1X_1 + b_2X_2 + b_3X_3 + b_4X_4 + b_5X_5 \quad (12)$$

Where:

Y = Utility of fast ships, ferries and aircrafts

X₁ = Cost effect

X₂ = Effect of travel time

X₃ = Influence of luggage

X₄ = Effect of weather

X₅ = Effect of comfort

Then made several alternative equations which are formed from the five independent variables to choose the best model equation. The best model equation criteria are illustrated by the value of R² Mc. Fadden. The greater the value of R² Mc. Fadden, the better the regression model equation is. Equations alternative that are formed along with the value of R² Mc. Fadden can be seen in Table 4 below:

Table 4. Equations Alternative That Are Formed Along With The Value Of R² Mc. Fadden

No.	Alternative	Form of Equations	R ² Mc. Fadden
1	Alternative 1	$y = a + b_1x_1$	0,731
2	Alternative 2	$y = a + b_2x_2$	0,314
3	Alternative 3	$y = a + b_3x_3$	0,513
4	Alternative 4	$y = a + b_4x_4$	0,070
5	Alternative 5	$y = a + b_5x_5$	0,059
6	Alternative 6	$y = a + b_1x_1 + b_2x_2$	0,782
7	Alternative 7	$y = a + b_1x_1 + b_3x_3$	0,851
8	Alternative 8	$y = a + b_1x_1 + b_4x_4$	0,765
9	Alternative 9	$y = a + b_1x_1 + b_5x_5$	0,758
10	Alternative 10	$y = a + b_2x_2 + b_3x_3$	0,660
11	Alternative 11	$y = a + b_2x_2 + b_4x_4$	0,382
12	Alternative 12	$y = a + b_2x_2 + b_5x_5$	0,327
13	Alternative 13	$y = a + b_3x_3 + b_4x_4$	0,537
14	Alternative 14	$y = a + b_3x_3 + b_5x_5$	0,527
15	Alternative 15	$y = a + b_4x_4 + b_5x_5$	0,128
16	Alternative 16	$y = a + b_1x_1 + b_2x_2 + b_3x_3$	0,940
17	Alternative 17	$y = a + b_1x_1 + b_2x_2 + b_4x_4$	0,833
18	Alternative 18	$y = a + b_1x_1 + b_2x_2 + b_5x_5$	0,810
19	Alternative 19	$y = a + b_1x_1 + b_3x_3 + b_4x_4$	0,860
20	Alternative 20	$y = a + b_1x_1 + b_3x_3 + b_5x_5$	0,868
21	Alternative 21	$y = a + b_1x_1 + b_4x_4 + b_5x_5$	0,797
22	Alternative 22	$y = a + b_2x_2 + b_3x_3 + b_4x_4$	0,722
23	Alternative 23	$y = a + b_2x_2 + b_3x_3 + b_5x_5$	0,691
24	Alternative 24	$y = a + b_3x_3 + b_4x_4 + b_5x_5$	0,555
25	Alternative 25	$y = a + b_1x_1 + b_2x_2 + b_3x_3 + b_4x_4$	0,946
26	Alternative 26	$y = a + b_1x_1 + b_2x_2 + b_3x_3 + b_5x_5$	0,941
27	Alternative 27	$y = a + b_1x_1 + b_2x_2 + b_4x_4 + b_5x_5$	0,891
28	Alternative 28	$y = a + b_1x_1 + b_3x_3 + b_4x_4 + b_5x_5$	0,929
29	Alternative 29	$y = a + b_2x_2 + b_3x_3 + b_4x_4 + b_5x_5$	0,726
30	Alternative 30	$y = a + b_1x_1 + b_2x_2 + b_3x_3 + b_4x_4 + b_5x_5$	0,953

Based on the Table 4 several equations alternative are produced, which have the largest value of R² Mc. Fadden is 0.953 as in the following equation 12:
 $Y = a + b_1X_1 + b_2X_2 + b_3X_3 + b_4X_4 + b_5X_5$

4.2 Simultaneous test

Based on the results of the analysis seen from Table 5, this test serves to determine the significant effect of independent variables on transportation mode selection decisions (dependent variable). The Examination Hypothesis is as follows:

- H₀ means that the independent variable does not affect the dependent variable
- H₁ means that at least one independent variable has a significant effect on the dependent variable

Table 5. Simultaneous test results

Model	Model Fitting Criteria	Likelihood Ratio Tests		
	-2 Log Likelihood	Chi-square	Df	Sig.
Intercept Only	218,577			
Final	4,558	214,019	62	0,000

H₀ hypothesis is rejected if the chi-square probability value is greater than the chi-square table and if the p-value ≤ α is 0.05. From the simultaneous test results in Table 5, it can be seen that the chi-square value is calculated at 214.019 while the chi-square table (0.05; 62) is 81.3376. This means that the chi-square count is greater than the chi-square table and also seen the p value of 0.000 < 0.05. Thus the H₀ hypothesis is rejected and states that at least one independent variable has a significant effect on the dependent variable or in other words, the overall independent variable influences the choice of transportation mode selection.

4.3 Partial test

The Likelihood Ratio Tests table in this test shows the contribution or influence of each independent variable on the transportation mode selection model. From the partial test results, it can be seen that the probability value smaller than alpha 5% is the variable influence of luggage (0.012), the influence of weather (0.038) and the influence of comfort (0.011). Then the variable that contributes to the model is the luggage, weather and comfort variables while the cost and travel time variable does not contribute to the model because it is not significant (p > 0.05).

Table 6. Likelihood ratio tests

Effect	Model Fitting Criteria	Likelihood Ratio Tests		
	-2 Log Likelihood of Reduced Model	Chi-square	Df	Sig.
Intercept	4,558	0,000	0	
Cost	9,965	5,407	4	0,248
Travel time	9,562	5,004	4	0,306
Luggage	7,551	2,993	4	0,012
Weather	7,192	2,634	6	0,038
Convenience	6,055	1,498	4	0,011

4.4 Model feasibility test

In Table 7 Goodness of Fit, provides information of the Model feasibility testing to state the difference between the frequency of observation with the frequency of expectations or in other words empirical data is suitable or not. It is expected that there is no difference between

the empirical data or the frequency of observation with the model or frequency of expectations. The model is said to be feasible if it is significantly above 0.05 and the chi-square value in the Deviance test is smaller than the chi-square table. If $D \leq X$ table (105,264), then H_0 is accepted. If $D \geq X$ table (105,264), then H_0 is rejected.

Table 7. Goodness of fit

	Chi-square	Df	Sig.
Pearson	65,164	88	0,142
Deviance	68,323	88	0,091

The results of Model feasibility test or Goodness of Fit can be seen in Table 7 From the table it is known that the value of D (68,323) \leq Xtable (105,264), then H_0 is accepted and the significance value is 0,091 above the alpha value of 0,05. It can be concluded that the model matches the empirical data or the multinomial logit model is suitable for use because a ood model is a model that accepts the null hypothesis.

4.5 Model equations of Kupang-rote selection mode

The logit function generated based on Table 8 parameter estimation is as follows:

Logit 1

$$U(\text{fast ship-aircraft}) = 0,437 + 0,054X_1 - 0,741X_2 - 1,951X_3 - 1,603X_4 + 2,197X_5$$

Logit 2

$$U(\text{ferry-aircraft}) = 0,652 + 0,129X_1 - 1,079X_2 + 2,125X_3 + 0,575X_4 - 2,059X_5$$

Table 8 Parameter estimates

Transportation Mode		B	Wald	Df	Sig.
Fast Ship	Intercept	0,437	0,700	1	0,403
	Cost (X1)	0,054	0,007	1	0,935
	Travel Time (X2)	-0,741	1,265	1	0,261
	Luggage (X3)	-1,951	6,117	1	0,013
	Weather (X4)	-1,603	4,680	1	0,031
	Comfort (X5)	2,197	3,709	1	0,054
Ferry	Intercept	0,652	1,611	1	0,204
	Cost (X1)	0,129	0,032	1	0,858
	Travel Time (X2)	-1,079	2,281	1	0,131
	Luggage (X3)	2,125	6,806	1	0,009
	Weather (X4)	0,575	0,578	1	0,447
	Comfort (X5)	-2,059	7,440	1	0,006

Description: Reference category = Airplane.

The variables that influence the model in logit function 1 and 2 are those that have a significance value of $p < 0.05$. In logit 1 function, the comparison between fast ships and aircraft shows that the variables that affect the modal selection model for the Kupang-Rote route are luggage variables and weather variables. Significant p value of each variable is p of luggage variable 0.013 < 0.05 and the weather variable significant p value 0.031 < 0.05 . The luggage variable has a lower influence on the

selection of fast boats compared to aircraft with a coefficient value of -1.951 and significant at $p (0.013) < 0.05$. The weather variable in the logit 1 function gives the effect of choosing a fast ship lower than the aircraft. Coefficient value of Weather variable -1.603 and significant at $p < 0.05$, means that when the weather is inadequate for sea transportation to be used, respondents will tend to choose a plane.

In logit 2 function, the comparison between ferry and aircraft shows that the variables that affect the modal selection model for the Kupang-Rote route are luggage variables and convenience variables. The significant value of p of luggage variable is 0.009 < 0.05 and significant p of the convenience variable is 0.006 < 0.05 . The luggage variable has a higher influence on the selection of ferry than the aircraft with a coefficient of 2.125 and a probability of 0.006 ($p < 0.05$). The convenience variable gives the effect of choosing a ferry boat lower than the aircraft with a coefficient value of -2.059 and a probability of 0.006 ($p < 0.05$). Based on logit 1 and 2 equation, the multinomial logistic regression model is obtained as follows:

$$\text{Fast Ship} = \frac{e^{0,437 - 1,951X_3 - 1,603X_4}}{1 + e^{0,437 - 1,951X_3 - 1,603X_4} + e^{0,652 + 2,125X_3 - 2,059X_5}}$$

$$\text{Ferry} = \frac{e^{0,652 + 2,125X_3 - 2,059X_5}}{1 + e^{0,437 - 1,951X_3 - 1,603X_4} + e^{0,652 + 2,125X_3 - 2,059X_5}}$$

$$\text{Aircraft} = \frac{1}{1 + e^{0,437 - 1,951X_3 - 1,603X_4} + e^{0,652 + 2,125X_3 - 2,059X_5}}$$

To find out the mode of transportation that has the greatest probability chosen by users of transportation services from Rote to Kupang, the estimated probability of response is used. The estimated probability of the response formed is as follows:

1. The probability of selecting a fast ship as a mode of transportation from Kupang to Rote:

$$\text{Fast Ship} = \frac{e^{0,437 - 1,951X_3 - 1,603X_4}}{1 + e^{0,437 - 1,951X_3 - 1,603X_4} + e^{0,652 + 2,125X_3 - 2,059X_5}} = 0,3465 = 34,65 \%$$

2. The probability of selecting a ferry as a mode of transportation from Kupang to Rote:

$$\text{Ferry} = \frac{e^{0,652 + 2,125X_3 - 2,059X_5}}{1 + e^{0,437 - 1,951X_3 - 1,603X_4} + e^{0,652 + 2,125X_3 - 2,059X_5}} = 0,4296 = 42,96 \%$$

3. The probability of selecting a aircraft as a mode of transportation from Kupang to Rote:

$$\text{Aircraft} = \frac{1}{1 + e^{0,437 - 1,951X_3 - 1,603X_4} + e^{0,652 + 2,125X_3 - 2,059X_5}} = 0,2238 = 22,38 \%$$

Based on the calculation of the transportation mode probability for the service route from Kupang to Rote, the results are obtained as above. Fast ship probability is 34.65%, ferry probability is 42.96% and aircraft probability is 22.38%. It is clearly known that of the three modes that have the largest probability of

selecting transportation mode is the ferry with a percentage of probability 42.96%.

4.6 Discussion of ferry, fast ships and aircraft users characteristics (Kupang-rote routes)

Based on the characteristics of ferry users analysis, fast ships and aircraft for both service routes shows the magnitude of movement in each of these modes. The form of the modal selection model for a service route as was done in this study, can provide the same or different results for each route. This is due to the presence of several influencing factors. Based on the results of research found that the factors group that influence the mode selection of Kupang-Rote are as follows:

- Characteristics of travelers

In this factor group, all variables relate to the individual of the traveler. The variables referred to include factors of gender, age, average monthly income and type of work. Based on the analysis results, several conclusions were drawn regarding the characteristics of ferry transportation, fast ship and aircraft users for both service routes and described as follows:

 - a. The effect of gender factors on the transportation characteristics users for both service routes describes different conditions. For the Kupang-Rote service route, male travelers generally prefer to use ferries while women prefer to use fast ships.
 - b. The influence of age factors on the characteristics of transportation users for both service routes illustrates the same conditions. The Kupang-Rote service route describes the characteristics of the travel agent dominated by transportation users in the age range of 20 to 39 years. This is because the age range is a productive age range that travels for work.
 - c. Most of the travelers who traveled from Kupang were earning less than one million rupiah per month. Most respondents who travel by ferry are respondents with income less than one million rupiah per month. Respondents who earn more than four million rupiah per month prefer to use airplanes, while average respondents that use fast ship earn less than one million rupiah, but the percentage is not as many as the ferry respondents.
 - d. The traveler from Kupang mostly came from the Civil Servants. Mode transportation that become a choice is a plane because of the comfort factor and travel time factor.

- Movement Characteristics

In this factor group, the existing variables influence travel agents in choosing modes of transportation. The intended variable is a travel intention factor. The characteristics of travelers from Kupang generally travel with the purpose of work and for family purposes. For work purposes, travelers from Kupang prefer to use planes because of the fast travel time and because of convenience. For the family events purpose, travelers from Kupang prefer to use ferries. This is because ferries provide cheap costs especially

if done in groups and can allow carrying large quantities of luggage and vehicles.

- Characteristics of transportation mode systems

In this factor group, all the variables in question give the influence of travel agents in choosing modes of transportation that are related to the facilities and performance of the transportation system services. These variables are factors of distance and travel time and travel costs. The characteristics of travelers from Kupang generally have to travel more than 10 km to get to the airport and port. To be able to get to the airport the traveler takes a travel time of less than 20 minutes and 20-40 minutes to get to their destination. To get to the ferry port (Bolok Port), the traveler takes more than 60 minutes to travel. Likewise, to get to the destination the traveler from Kupang who uses a ferry boat takes 40-60 minutes. Similarly, to get to their destination, fast boat users to Rote need 20-40 minutes to their destination.

4.7 Discussion of the selection model with the users characteristics relationship

Based on the results of the logit multinomial analysis conducted for the Kupang-Rote route, there are three probability equations model for each service route. Result of the equations and probabilities are as follows:

$$\begin{aligned}
 \text{a. Kapal cepat} &= \frac{e^{0,437 - 1,951X_3 - 1,603X_4}}{1 + e^{0,437 - 1,951X_3 - 1,603X_4} + e^{0,652 + 2,125X_3 - 2,059X_5}} \\
 &\text{Probabilitas pemilihan kapal cepat } 34,65 \% \\
 \text{b. Kapal feri} &= \frac{e^{0,652 + 2,125X_3 - 2,059X_5}}{1 + e^{0,437 - 1,951X_3 - 1,603X_4} + e^{0,652 + 2,125X_3 - 2,059X_5}} \\
 &\text{Probabilitas pemilihan kapal feri } 42,96 \% \\
 \text{c. Pesawat} &= \frac{1}{1 + e^{0,437 - 1,951X_3 - 1,603X_4} + e^{0,652 + 2,125X_3 - 2,059X_5}} \\
 &\text{Probabilitas pemilihan pesawat } 22,38 \%
 \end{aligned}$$

Where:

- X₁ = Effect of costs
- X₂ = Effect of travel time
- X₃ = factor of luggage
- X₄ = weather factor
- X₅ = comfort factor

Judging from the model of equations that are formed, the factors that influence the choice of transportation modes from Kupang are luggage, weather and comfort factors. The luggage factor influences the choice of mode between ferries, fast ship and aircraft because each transportation mode has a different luggage capacity limit for passenger. Luggage capacity on aircraft is limited to each person is 15 kg while ferries and fast boats do not have luggage capacity limits for each passenger. However, ferries have the advantage of being able to carry vehicles while fast boats are not possible. This causes the luggage factor gives an influence on the mode transportation choice.

The next factors that gives effect to the probability model of mode selection is weather. The weather factor influences the choice of mode because the available

transportation modes to connect between Rote and Kupang are sea transportation modes and air transportation modes. In certain months such as January-February and June-August, weather influences do not support the use of sea transportation due to high winds and high sea waves. Travelers who travel in these months will generally switch modes from sea transportation to air transportation (aircraft). This also makes travelers think that the comfort level of the aircraft is higher than the other transportation modes.

Based on the influence of luggage, weather and comfort factors on the model of modal selection for Kupang-Rote route, a large probability for each mode of transportation is obtained. The highest probability value for the Kupang-Rote route is on a ferry with a percentage of 42.96%.

5 Conclusions

1. Users of transportation services from Kupang in the direction of Rote, in general men prefer to use ferry women prefer to use fast boats. The characteristics of respondents for travel is ages period of 20-39 years. The average user of this service comes from Government employee. There are people who travel for work and events for families. When traveling, on average you have to travel more than 10 km to get to the airport and port.
2. Factors that influence the choice of transportation modes between ferries, fast boats and planes both Kupang-Rote are luggage, weather and comfort. Luggage is the reason for ferries and fast boats to be more dominant. While climate and comfort are the reasons for choosing a plane. Kupang-Rote service route
3. Utility function model of mode selection between fast ships, ferries and aircraft are as follows:
Ufast ship – aircraft = $0,437 + 0,054X_1 - 0,741X_2 - 1,951X_3 - 1,603X_4 + 2,197X_5$
Uferry – aircraft = $0,652 + 0,129X_1 - 1,079X_2 + 2,125X_3 + 0,575X_4 - 2,059X_5$
Logistic multinomial model:
Fast ship= The probability of fast ship selection is 34.65%
Ferries= The probability of ferry selecting is 42.96%
Plane= The probability of plane selecting is 22.38%

References

1. H. Abulebu, *Studi Pemilihan Moda Untuk Perjalanan Antar Kota Rute Poso-Makasar*, Program Pascasarjana Universitas Hasanudin, Makasar (2013)
2. J. Black, *Urban Transport Planning*, London, Croom Helm (1981)
3. G. Gordon, *System Simulation, 2nd edition*. Prentice Hall, Englewood Cliffs, New Jersey (1978)
4. F. Miro, *Perencanaan Transportasi*, Jakarta: Erlangga (2005)
5. Sugiyono, *Statistika Untuk Penelitian*. Bandung: CV Alfabeta (2007)
6. T.M. Simatupang, *Pemodelan Sistem*. Nindita: Klaten (1995)
7. R. Simanjuntak, *Analisa Pemilihan Moda Transportasi Medan-Rantau Prapat Dengan Menggunakan Metode Stated Preference*, Jurusan Teknik Sipil Fakultas Teknik Universitas Sumatera Utara. Medan (2011)