

The optimal placement model for electric vehicle charging stations using bayesian networks

M Sai Siddarth Reddy^{1*}, B Sai Venkata Nitin¹ and Garlapati Narayana¹

¹Department of AI&ML, CBIT, Hyderabad, Telangana, India.

Abstract. As costs rise and fossil fuels have harmful environmental effects more and more people choose electric cars or electric cars this change shows how electric cars are becoming more and more popular in the transportation industry as their fleet grows it becomes clear that more infrastructure is required for charging the first step in the optimization method of this study which aims to identify ideal locations for stations considering user accessibility and investment costs is to identify potential charging locations and places are carefully studied using mixed integer linear programming MLP techniques to identify optimal locations based on historical EV paths the study examines this complex urban environment.

Keywords. Electric Vehicle, Charging Station Placement, Optimization

1 Introduction

The raising dependence on fossil fuels underscores the limited nature of their accessibility with figures anticipating savings to decrease by 2050, thus lattice frameworks are advancing towards coordination electric vehicles EVs as portion of a broader innovative thrust towards maintainability concerns with respect to vitality shortage and climate alter have impelled the selection of EVs coming about in a consistent uptick in their utilization from a natural point of view. The far reaching grasp of EVs holds the guarantee of considerably diminishing nursery gas outflows projections from different thinks about propose that EVs may contain up to 70 of all vehicles by 2050 signaling a critical move towards cleaner portability options in spite of the complex benefits of EVs challenges, such as restricted driving extend hold on compared to conventional vehicles be that as it may progressions in battery innovation have empowered EVs to cover longer separations on a single charge yet requiring normal energizing.

This underscores the pressing require for a well-structured arrange of charging stations deliberately found to meet the surging request at the beginning of this activity the essential objective was to optimize the vicinity between EVs and charging stations

* Corresponding author: siddu26.reddy@gmail.com

guaranteeing both reasonableness and availability ventures are channeled towards creating charging foundation and installment components adapted towards cultivating consistent EVs integration and relieving appropriation obstructions

2 Literature Survey

Because multiple electric vehicles use electric charging stations at the same time, it is important to place these stations in high-traffic areas in order to reduce the total cost of the equipment needed for fast-charging as well as the cumulative losses to the distribution network. [1] This study used Particle Swarm Optimization to optimize the placement of electric vehicle (EV) charging stations in Jordan. It considered factors such as transformer loading, distribution lines, system voltage, and losses. However, it did not consider the type of EV charger or charging stations that were not on the route, and it did not account for investment costs. [2] This research aimed to minimize the total distance traveled for EV charging stations using the shortest path algorithm. It considered investment costs of charging stations in different city locations and stations not directly on the route. However, it did not account for the type of EV charger or voltage profiles of the grid. [3]The paper explored various smart charging strategies, such as network-oriented, renewable energy-oriented, and cost-oriented charging, which can enhance system stability, grid functioning, and reduce infrastructural investments. The limitation includes the requirement for sufficient renewable energy capacity to meet additional electricity demand from EVs. [4]This research focused on iterative mathematical optimization techniques and prioritized human factors over technological ones for charging station placement. The study didn't explicitly mention strengths or limitations, but it's essential to consider potential technical and grid-related factors. [5] Using Mixed-Integer Programming and a stress test, this study found that increasing the number of charging stations reduced the inconvenience experienced by vehicles. However, it couldn't analyze the geographical and time-based impacts of EV charging on the power grid.

3 Methodology

3.1 Swarm Optimization

Swarm optimization is an optimization technique inspired by nature that is based on the collective behavior of social organisms such as ants, bees, and birds. It entails a population of agents (particles) that move through a search space iteratively adjusting their positions to find the best solution. The agents communicate with one another and share information about their best-known positions, allowing the swarm to converge on the best solution. Swarm optimization methods include popular algorithms such as Particle Swarm Optimization (PSO) and Ant Colony Optimization (ACO). Swarm optimization is especially useful for solving complex, high-dimensional, and non-convex optimization problems that traditional methods may struggle with.

3.2 Mixed-Integer Linear Programming (MILP)

MILP is a mathematical optimization technique used to solve problems with discrete and continuous variables, where some variables are restricted to take integer values. It is widely applied in various fields, including engineering, economics, and logistics, to model

decision-making problems with both discrete and continuous aspects. MILP problems are formulated as linear equations and inequalities, but with the additional constraint that certain variables must be integers. Solving MILP problems can be computationally demanding, and specialized solvers like CPLEX and Gurobi are often used for efficient solutions. MILP finds applications in production planning, resource allocation, supply chain management, and many other domains with discrete decision variables.

3.3 Bayesian Network

Bayesian networks often referred to as belief networks or bayes nets serve as probabilistic graphical models designed to illustrate the probabilistic connections within a set of variables these networks utilize directed acyclic graphs dags to represent dependencies among variables with nodes denoting random variables and edges expressing probabilistic associations each node in the graph is linked to a conditional probability distribution that defines the likelihood of the variable assuming a particular value based on the values of its parent nodes employed extensively in artificial intelligence machine learning and decision support systems bayesian networks are instrumental for modeling uncertainty conducting reasoning under uncertain conditions and making probabilistic inferences they offer a robust framework for capturing intricate dependencies in real-world systems finding applications in diverse domains such as medical diagnosis finance and risk assessment

3.4 Greedy Approach

The greedy approach is a heuristic strategy that makes locally optimal choices at each step with the hope of finding a global optimum. It is simple, intuitive, and computationally efficient, making it useful for solving problems where finding an exact solution is impractical. However, the greedy approach does not always guarantee the best solution and may lead to suboptimal results in some cases. Greedy algorithms are commonly employed in problems like the knapsack problem, scheduling tasks, and constructing minimum spanning trees. Despite its limitations, the greedy approach can be a powerful tool when used appropriately and can provide near-optimal solutions for certain types of problems.

4 Conclusion

This study makes a plan arrange that coordinating both future charging alternatives and renewable vitality into the electrical framework introducing disseminated era is cheap. Since it maintains a strategic distance from the expansion of dissemination lines and the development of fossil fills integration procedures such as misfortune admonishment top stack shedding list administration and venture delay can offer assistance arrange the areas and measure of conveyed era. This synchronous ideal EV charging framework plan gives a total framework plan arrangement and as a result we have made a strong and user-friendly strategy for finding EV charging stations in expansion this think about bargains with the issueof area of charging stations.

In Indian cities future investigate within the field can address a few basic issues related to charging framework plan such as charging station estimating techniques vehicle-to-network charging station plan superior integration of renewable vitality partners and maximizing income

References

1. Optimal Placement of Electric Vehicle Charging Stations: A Case Study in Jordan. <https://ieeexplore.ieee.org/document/10078486>.
2. Techniques for optimal Placement of Electric Vehicle Charging Stations: A review <https://ieeexplore.ieee.org/document/10085887>.
3. Optimal Placement of Electric Vehicle Charging Station with V2G Provision using Symbiotic Organisms Search Algorithm. <https://ieeexplore.ieee.org/document/9740988>.
4. The Optimal Placement Model for Electric Vehicle Charging Stations <https://ieeexplore.ieee.org/document/8882651>.
5. Optimal Siting and Sizing Approach of Plug-in Electric Vehicle Fast Charging Station using a Novel Meta-heuristic Algorithm. <https://ieeexplore.ieee.org/document/9847926>
6. Electric mobility in Europe – Future impact on the emissions and the energy system, Oeko-Institut and Transport Mobility Leuven(TML), 2016
7. A. Y. S. Lam, Y. W. Leung and X. Chu, “Electric Vehicle Charging Station Placement: Formulation, Complexity, and Solutions”, IEEE Transactions on Smart Grid, vol. 5, no. 6, pp. 2846-2856, Nov. 2014.
8. EU energy, transport and GHG emissions: Trends to 2050, ‘PRIMES model for energy and CO2 emissions projections, Reference scenario 2013’, European Commission, Directorate- General for Energy,
9. M. Andrews, M. K. Dogru, J. D. Hobby, G. H. Tucci, and Y. Jin,” Modeling and Optimization for Electric Vehicle Charging Infrastructure,” Alcatel-Lucent Bell Labs, 2012.
10. J. Lorfberg, “YALMIP: A Toolbox for Modeling and Optimization in MATLAB,” In Proceedings of the CACSD.
11. Moupuri Satish Kumar Reddy; K. Selvajothi - Optimal Placement of Electric Vehicle Charging Stations in Radial Distribution System for along with Reconfiguration.
12. M. Mohammadi, F. Jolai and H. Rostami, “An M/M/c queue model for hub covering location problem,” Math. Comput. Model., vol 54, nos. 11-12, pp 2623-2628,2011.